

THE ARTHREX Compression FT

The zero-profile, headless, titanium 2.5 Micro Compression FT™, 3.5 Mini Compression FT™, and 4.0 Standard Compression FT Screws can be used for a wide range of indications in the upper and lower extremities.



Key Features and Benefits:

- **Variable-Stepped Thread Pitch** – Screw design supports gradual compression of fragments
- **Headless** – Can be implanted intra-articularly and extra-articularly with minimal risk of impingement or soft-tissue irritation
- **Self-drilling and Self-tapping** – Two sets of cutting flutes facilitate insertion
- **Multiple Size Options** – The screws are available in 2.5 Micro, 3.5 Mini, and 4.0 Standard sizes
- **Cannulation** – Assists in accurate placement for both percutaneous and open indications
- **Improved Torque Transmission** – Hexalobe recess in 3.5 and 4.0 Compression FT screws provide improved torque transmission. *Note: 2.5 screw has 1.5 mm hex driver*



Ordering Information

Compression FT Screw System Set (AR-8738S) includes:

Depth Device	AR-8737-51
Obturator for Drill Guide	AR-8737-44
Percutaneous Drill Guide	AR-8737-43
Screwdriver Handle, ratcheting	AR-8950RH
Guidewire Plunger	AR-8737-56
Screw Holding Forceps	AR-8941F
Percutaneous Pin Clamp	AR-8737-57
Screw Caddy	AR-8738C

2.5 Micro Compression FT™ Screws

Drill Bit, straight, cannulated, 2.0 mm	AR-8737-34
Drill Bit, straight, cannulated, 2.2 mm (hard bone option)	AR-8737-58
Driver, cannulated, 1.5 mm hex	AR-8737-37
Driver Shaft, solid, 1.5 mm hex	AR-8737-45
Profile Drill, Micro	AR-8737-46
Parallel Drill Guide	AR-8737-48

3.5 Mini Compression FT™ Screws

Drill Bit, straight, cannulated, 2.7 mm	AR-8737-35
Driver, cannulated, T10 Hexalobe	AR-8737-38
Driver Shaft, T10 Hexalobe	AR-8950SD-10
Profile Drill, Mini	AR-8737-47
Parallel Drill Guide	AR-8737-49

4.0 Standard Compression FT Screws

Drill Bit, straight, cannulated, 3.2 mm	AR-8737-50
Driver, cannulated, T10 Hexalobe	AR-8737-38
Driver Shaft, T10 Hexalobe	AR-8950SD-10
Profile Drill, Standard	AR-8737-54
Parallel Drill Guide	AR-8737-55

Implants:

2.5 Micro Compression FT Screws*

8 mm-14 mm (1 mm increments)	AR-8725-08H – 14H
16 mm-30 mm (2 mm increments)	AR-8725-16H – 30H

3.5 Mini Compression FT Screws*

12 mm-34 mm (2 mm increments)	AR- 8730-12H – 34H
-------------------------------	--------------------

4.0 Standard Compression FT Screws

16 mm-50 mm (2 mm increments)	AR- 8740-16H – 50H
-------------------------------	--------------------

Disposables (not included in set):

2.5 Micro Compression FT Screws

Guidewire w/Trocar Tip, 0.034" (0.86 mm), laser-marked	AR-8737-39
Guidewire w/ double Trocar Tip, 0.034" (0.86 mm), laser-marked	AR-8737-39KD
Guidewire, w/Trocar Tip, threaded, 0.034" (0.86 mm), laser-marked	AR-8737-40

3.5 Mini and 4.0 Standard Compression FT Screws

Guidewire w/Trocar Tip, 0.045" (1.1 mm), laser-marked	AR-8737-41
Guidewire w/ double Trocar Tip, 0.045" (1.1 mm), laser-marked	AR-8737-41KD
Guidewire w/Trocar Tip, threaded, 0.045" (1.1 mm), laser-marked	AR-8737-42

Optional:

Compression FT Screw System Caddy, Common Instruments	AR-8738C-01
Compression FT Screw System Caddy, Micro	AR-8738C-02
Compression FT Screw System Caddy, Mini	AR-8738C-03
Compression FT Screw System Caddy, Standard	AR-8738C-04

*2.5 Micro and 3.5 Mini Compression FT screws and instrumentation are also available in the QuickFix™ cannulated screw set (AR-8737S)

